



- + High energy efficiency
- + Dramatically smaller footprint
- + Effortless charging experience
- + Minimal maintenance
- + Maximum uptime
- + IP65

PK350/350kW Specifications

INNOVATING YOUR FUTURE



USER UNIT

CONNECTORS	CCS Type 2 and CHAdeMO Single or dual cable option
OUTPUT POWER	Up to 350kW
OUTPUT VOLTAGE	Up to 920V DC
OUTPUT CURRENT	CCS: Up to 500A CHAdeMO: Up to 200A
IP RATING	IP65
EFFICIENCY	98.5% typ
MAXIMUM OPERATING ALTITUDE	2,000m (6,562 ft)
OPERATING TEMPERATURE	-35°C to 50°C (-31°F to 122°F)
CREDIT CARD READER	Optional
DIMENSIONS	2,000mm (6'7") (H) x 980mm (3'3") (W) x 525mm (1'8" in) (D)
WEIGHT	320kg (706lb) dual cable
RFID READER	MIFARE ISO/IEC14443A/B, ISO/IEC15693, ISO/IEC18000-3, FeliCa, NFC, EMV 2.0
CABLE REACH	4.1m (13'5")
IK RATING	IK10

A U S T R A L I A • U S A • E U R O P E

tritium.com.au • enquiries@tritium.com.au

Worldwide +61 7 3147 8500 • 48 Miller Street, Murarrie, QLD 4172, Australia

USA +1 310 961 5299 • 20000 Vermont Avenue, Torrance, CA 90503, United States

Europe +31 202 250 100 • Luchtvaartstraat 3B, 1059 CA Amsterdam, Netherlands

Veefil® is a registered trademark of Tritium Pty Ltd. © 2020 Tritium Pty Ltd

POWER UNIT

INPUT	2 X 480V 3ph 50Hz
OUTPUT	2 X 950V DC 355kW
IP RATING	IP54
EFFICIENCY	>98% typ
POWER FACTOR	0.99
MAXIMUM OPERATING ALTITUDE	2,000m (6562 ft)
OPERATING TEMPERATURE	-35°C to 50°C (-31°F to 122°F)
NETWORK CONNECTION	Ethernet to User Unit and Control Unit Site Power Control
WEIGHT	593kg (1,308lb)
DIMENSIONS	2,310mm (7'7") (H) x 610mm (2') (W) x 1060mm (3'6") (D)
THD	<5%
IK RATING	IK10

CONTROL UNIT

WIRELESS CONNECTIVITY	3G/4G cellular communications with failover redundancy
WIRED CONNECTIVITY	Ethernet capability
POWER SUPPLY	Battery-backed UPS functionality for reliable telemetry at all times
SOFTWARE SUPPORT	OCPPI.6J support for management and billing
IT SECURITY	SSH with EC keys & unique password for manufacturer diagnostics
POWER SHARING	Configurable site-level power demand management
POWER CONTROL	Power sharing algorithms can be easily added and modified to allow for various sharing configurations
CONTROL PLATFORM	Gives owner/operators vital real-time information on the status and performance of the charging station
MAXIMUM OPERATING ALTITUDE	2,000m (6562 ft)
WEIGHT	220kg (485lb)
DIMENSIONS	2,310mm (7'7") (H) x 610mm (2') (W) x 1060mm (3'6") (D)
IK RATING	IK10
TEMPERATURE RATING	-35°C to 50°C (-31°F to 122°F)
VOLTAGE INPUT	230V +/- 10%
IP RATING	IP54